

IN THE CLAIMS

1. A multicast network management method, comprising the steps of:

5 generating a packet-tracking queue with individual entries representing datapackets for transfer through a hierarchical network;

 storing an actual multicast datapacket and its real payload in a first-in, first-out (FIFO) buffer;

10 expanding any packet-tracking queue entry representing a multicast datapacket into several consecutive entries, one each for the individual subscribers enrolled to receive a broadcast, and wherein, each expanded entry is subject to its own unique bandwidth-allocating service-level
15 policy;

 flagging a first of such expanded entries as being first, and flagging a last such expanded entry as being last; and

20 releasing and clearing said datapackets in any order, and if the first or last are released, then the next or previous are marked as first or last;

 wherein, individually delayed releases of duplicated multicast datapackets enforce a bandwidth limiting function of any service-level policies involved.

25

2. The method of claim 1, further comprising the step of:

 checking to see if only a single-remaining expanded entry is left by seeing if it is flagged as being both first
30 and last.

1000409-112701

3. The method of claim 2, further comprising the steps of:

releasing said single-remaining expanded entry; and
clearing said packet-tracking queue and said actual
5 datapacket and its real payload in said FIFO buffer.

4. The method of claim 1, further comprising the steps of:

associating a service-level policy that limits
10 allowable bandwidths to particular nodes in a hierarchical
network;

classifying datapackets moving through said
hierarchical network according to a particular service-level
policy;

15 managing all datapackets moving through said
hierarchical network from a variable-depth queue in which
each queue entry includes service-level policy bandwidth
allowance for a node in said network through which a
corresponding datapacket must pass;

20 repeatedly scanning said variable-depth queue to
determine whether a datapacket should be forwarded through
said node by checking for enough bandwidth-allocation
credits; and

replenishing an account of said bandwidth-
25 allocation credits taking into account a variable delay
caused by scanning said variable-depth queue.

5. The method of claim 4, further comprising the step of:

30 testing in parallel whether a particular datapacket
should be delayed in a buffer or sent along for every
hierarchical node in said network through which it must pass.

10004079-112704

6. The method of claim 4, further comprising the step of:

constructing a single queue of entries associated with corresponding datapackets passing through said hierarchical network such that each entry includes source and destination header information and a list of any available bandwidth credits for every hierarchical node in said network through which a corresponding datapacket must pass.

7. A hierarchical network for use with multicast, comprising:

means for generating a packet-tracking queue with individual entries representing datapackets for transfer through a hierarchical network;

means for storing an actual multicast datapacket and its real payload in a first-in, first-out (FIFO) buffer;

means for expanding any packet-tracking queue entry representing a multicast datapacket into several consecutive entries, one each for the individual subscribers enrolled to receive a broadcast, and wherein, each expanded entry is subject to its own unique bandwidth-allocating service-level policy;

means for flagging a first of such expanded entries as being first, and flagging a last such expanded entry as being last;

means for releasing and clearing said datapackets in any order, and if the first or last are released, then the next or previous are flagged as being first or last;

means for checking to see if only a single-remaining expanded entry is left by seeing if it is flagged as being both first and last;

means for releasing said single-remaining expanded entry; and

means for clearing said packet-tracking queue and said actual datapacket and its real payload in said FIFO
5 buffer;

wherein, individually delayed releases of multicast datapackets enforce a bandwidth limiting function of any service-level policies involved at independent network nodes.

10 8. The network of claim 7, further comprising:

means for associating a service-level policy that limits allowable bandwidths to particular nodes in a hierarchical network;

15 means for classifying datapackets moving through said hierarchical network according to a particular service-level policy;

20 means for managing all datapackets moving through said hierarchical network from a variable-depth queue in which each node entry includes service-level policy bandwidth allowance for a node in said network through which a corresponding datapacket must pass;

25 means for repeatedly scanning said variable-depth queue to determine whether a datapacket should be forwarded through said node by checking for enough bandwidth-allocation credits; and

means for replenishing an account of said bandwidth-allocation credits taking into account a variable delay caused by scanning said variable-depth queue.

30 9. The means of claim 8, further comprising:

means for testing in parallel whether a particular datapacket should be delayed in a buffer or sent along for

10004079-112701

every hierarchical node in said network through which it must pass.

10. The means of claim 8, further comprising:

5 means for constructing a single queue of entries associated with corresponding datapackets passing through said hierarchical network such that each entry includes source and destination header information and a list of any available bandwidth credits for every hierarchical node in
10 said network through which a corresponding datapacket must pass.

11. A network management system, comprising:

a protocol processor providing for header
15 inspection of datapackets circulating through a network and providing for an information output comprising at least one of source IP-address, destination IP-address, port number, and application type;

a classifier connected to receive said information
20 output and able to associate a particular datapacket with a particular network node and a corresponding service-level policy bandwidth allowance;

a variable-depth queue comprising individual
25 entries related to said datapackets circulating through said network, and further related to a network node through which each must pass;

a replicator for duplicating datapackets in a
multicast stream for each enrolled subscriber, and able to expand the variable-depth queue with expanded multicast
30 entries; and

a traffic-shaping cell providing for an inspection of each one of said individual entries and for outputting a

10004079-112701
T0221" 52040001

single decision whether to pass through or buffer each of said datapackets in all network nodes through which each must pass;

5 wherein, individually delayed releases of multicast datapackets enforce a bandwidth limiting function of any service-level policies involved.

12. The system of claim 11, further comprising:
an output scheduler and marker for scheduling a
10 released datapacket for output, and for marking it according to an output received from the traffic-shaping cell.

13. The system of claim 11, further comprising:
at least one of the protocol processor, classifier,
15 replicator, and traffic-shaping cell, are implemented as a semiconductor intellectual property and operate at run-time with the variable-depth queue.

10004079.112701